

CSCI 104

List ADT & Array-based Implementations Queues and Stacks

Mark Redekopp

David Kempe

Lists

- Ordered collection of items, which may contain duplicate values, usually accessed based on their position (index)
 - Ordered = Each item has an index and there is a front and back (start and end)
 - Duplicates allowed (i.e. in a list of integers, the value 0 could appear multiple times)
 - Accessed based on their position (list[0], list[1], etc.)
- What are some operations you perform on a list?



List Operations

Operation	Description	Input(s)	Output(s)
insert	Add a new value at a particular location shifting others back	Index : int Value	
remove	Remove value at the given location	Index : int	Value at location
get / at	Get value at given location	Index : int	Value at location
set	Changes the value at a given location	Index : int Value	
empty	Returns true if there are no values in the list		bool
size	Returns the number of values in the list		int
push_back / append	Add a new value to the end of the list	Value	
find	Return the location of a given value	Value	Int : Index

IMPLEMENTATIONS

Implementation Strategies

- Linked List
 - Can grow with user needs
- Bounded Dynamic Array
 - Let user choose initial size but is then fixed
- Unbounded Dynamic Array
 - Can grow with user needs

BOUNDED DYNAMIC ARRAY STRATEGY

A Bounded Dynamic Array Strategy

- Allocate an array of some user-provided size
- What data members do I need?
- Together, think through the implications of each operation when using a bounded array (what issues could the fact that it is bounded cause)?

```
#ifndef BALISTINT_H
#define BALISTINT_H

class BAListInt {
public:
    BAListInt(unsigned int cap);

    bool empty() const;
    unsigned int size() const;
    void insert(int pos,
                const int& val);
    bool remove(int pos);
    int& const get(int loc) const;
    int& get(int loc);
    void set(int loc, const int& val);
    void push_back(const int& val);
private:

};
#endif
```

balistint.h

A Bounded Dynamic Array Strategy

- What data members do I need?
 - Pointer to Array
 - Current size
 - Capacity
- Together, think through the implications of each operation when using a static (bounded) array
 - Push_back: Run out of room?
 - Insert: Run out of room, invalid location

```
#ifndef BALISTINT_H
#define BALISTINT_H

class BAListInt {
public:
    BAListInt(unsigned int cap);

    bool empty() const;
    unsigned int size() const;
    void insert(int pos,
                const int& val);
    void remove(int pos);
    int const & get(int loc) const;
    int& get(int loc);
    void set(int loc, const int& val);
    void push_back(const int& val);
private:
    int* data_;
    unsigned int size_;
    unsigned int cap_;
};
#endif
```

balist.h

Implementation

- Implement the following member functions
 - A picture to help write the code

0	1	2	3	4	5	6	7
30	51	52	53	54	10		

```
BAListInt::BAListInt (unsigned int cap)
{

}

void BAListInt::push_back(const int& val)
{

}

void BAListInt::insert(int loc, const int& val)
{

}

}
```

balist.h (cont)

Implementation (cont.)

- Implement the following member functions
 - A picture to help write the code

0	1	2	3	4	5	6	7
30	51	52	53	54	10		

```
void BAListInt::remove(int loc)
{

}
}
```

balist.h

Const-ness

- What functions stand out as looking strange?

```
#ifndef BALISTINT_H
#define BALISTINT_H

class BAListInt {
public:
    BAListInt(unsigned int cap);

    bool empty() const;
    unsigned int size() const;
    void insert(int pos,
                const int& val);
    bool remove(int pos);

    int& const get(int loc) const;
    int& get(int loc);

    void set(int loc, const int& val);
    void push_back(const int& val);
private:

};
#endif
```

Const-ness

- What functions stand out as looking strange?
- Two versions of get()
- Why do we need two versions of get?
- Because we have two use cases...
 - 1. Just read a value in the array w/o changes
 - 2. Get a value w/ intention of changing it

```
#ifndef BALISTINT_H
#define BALISTINT_H

class BAListInt {
public:
    BAListInt(unsigned int cap);

    bool empty() const;
    unsigned int size() const;
    void insert(int pos,
                const int& val);
    bool remove(int pos);


    int& const get(int loc) const;
    int& get(int loc);

    void set(int loc, const int& val);
    void push_back(const int& val);
private:

};
#endif
```


Constness

```
// ---- Recall List Member functions ----  
// const version  
int& const BAListInt::get(int loc) const  
{ return data_[i]; }  
  
// non-const version  
int& BAListInt::get(int loc)  
{ return data_[i]; }  
  
void BAListInt::insert(int pos, const int& val);  
  
// ---- Now consider this code ----  
void f1(const BAListInt& mylist)  
{  
    // This calls the const version of get  
    // w/o the const-version this would not compile  
    // since mylist was passed as a const parameter  
    cout << mylist.get(0) << endl;  
    mylist.insert(0, 57); // won't compile..insert is non-const  
}  
  
int main()  
{  
    BAListInt mylist;  
    f1(mylist);  
}
```



Returning References

```
// ---- Recall List Member functions ----  
// const version  
int& const BAListInt::get(int loc) const  
{ return data_[i]; }  
  
// non-const version  
int& BAListInt::get(int loc)  
{ return data_[i]; }  
  
void BAListInt::insert(int pos, const int& val);  
  
// ---- Now consider this code ----  
void f1(BAListInt& mylist)  
{  
    // This calls the non-const version of get  
    // if you only had the const-version this would not compile  
    // since we are trying to modify what the  
    // return value is referencing  
    mylist.get(0) += 1; // equiv. mylist.set(mylist.get(0)+1);  
    mylist.insert(0, 57);  
    // will compile since mylist is non-const  
}  
  
int main()  
{ BAListInt mylist;  
  f1(mylist);  
}
```




- **Moral of the Story: We need both versions of get()**

UNBOUNDED DYNAMIC ARRAY STRATEGY

Unbounded Array

- Any bounded array solution runs the risk of running out of room when we insert() or push_back()
- We can create an unbounded array solution where we allocate a whole new, larger array when we try to add a new item to a full array



We can use the strategy of allocating a new array **twice** the size of the old array

Activity

- What function implementations need to change if any?

```
#ifndef ALISTINT_H
#define ALISTINT_H

class AListInt {
public:
    bool empty() const;
    unsigned int size() const;
    void insert(int loc,
               const int& val);
    void remove(int loc);
    int& const get(int loc) const;
    int& get(int loc);
    void set(int loc, const int& val);
    void push_back(const T& new_val);
private:

    int* _data;
    unsigned int _size;
    unsigned int _capacity;
};

// implementations here
#endif
```

Activity

- What function implementations need to change if any?

```
#ifndef ALISTINT_H
#define ALISTINT_H

class AListInt {
public:
    bool empty() const;
    unsigned int size() const;
    void insert(int loc,
               const int& val);
    void remove(int loc);
    int& const get(int loc) const;
    int& get(int loc);
    void set(int loc, const int& val);
    void push_back(const T& new_val);
private:
    void resize(); // increases array size
    int* _data;
    unsigned int _size;
    unsigned int _capacity;
};

// implementations here
#endif
```

A Unbounded Dynamic Array Strategy

- Implement the `push_back` method for an unbounded dynamic array

```
#include "alistint.h"

void AListInt::push_back(const int& val)
{

}

}
```

alistint.cpp

Specialized Lists

STACKS AND QUEUES

Stacks & Queues

- Lists are good for storing generic sequences of items, but they can be specialized to form other useful structures
- What if we had a List, but we restricted how insertion and removal were done?
 - **Stack** – Only ever insert/remove from one end of the list
 - **Queue** – Only ever insert at one end and remove from the other

First-In, First-Out (FIFOs)

QUEUE ADT

Queue ADT

- Queue – A list of items where insertion only occurs at the back of the list and removal only occurs at the front of the list
 - Like waiting in line for a cashier at a store
- Queues are FIFO (First In, First Out)
 - Items at the back of the queue are the newest
 - Items at the front of the queue are the oldest
 - Elements are processed in the order they arrive

A Queue Visual


Items leave from the front
(pop_front)



Items enter at the back
(push_back)



(pop_front)




(push_back)



Queue Operations

- What member functions does a Queue have?
 - `push_back(item)` – Add an item to the back of the Queue
 - `pop_front()` - Remove the front item from the Queue
 - `front()` - Get a reference to the front item of the Queue (don't remove it though!)
 - `size()` - Number of items in the Queue
 - `empty()` - Check if the Queue is empty



A Queue Class

- A sample class interface for a Queue
- Queue Error Conditions
 - **Queue Underflow** – The name for the condition where you call pop on an empty Queue
 - **Queue Overflow** – The name for the condition where you call push on a full Queue (a Queue that can't grow any more)
 - This is only possible for Queues that are backed by a bounded list

```
#ifndef QUEUEINT_H
#define QUEUEINT_H

class QueueInt {
public:
    QueueInt();
    ~QueueInt();
    int size() const;
    void push_back(const int& value); //enqueue
    void pop_front(); // dequeue
    int const & front() const;
    bool empty() const;
private:
    // ???
};
#endif
```

Other Queue Details

- How should you implement a Queue?
 - Back it with an ArrayList
 - Back it with a linked list
 - Back it with a vector
 - Inherit from a linked list
 - Which is best?

	Push_back	Pop_front	Front()
ArrayList			
LinkedList (Singly-linked w/ tail ptr)			
LinkedList (Singly-linked w/o tail ptr)			

Other Queue Details

- How should you implement a Queue?
 - Back it with an ArrayList
 - Back it with a linked list
 - Back it with a vector
 - Inherit from a linked list
 - Which is best?

	Push_back	Pop_front	Front()
ArrayList	$O(1)$	$O(n)$	$O(1)$
LinkedList (Singly-linked w/ tail ptr)	$O(1)$	$O(1)$	$O(1)$
LinkedList (Singly-linked w/o tail ptr)	$O(n)$	$O(1)$	$O(1)$

Queue Applications


- Print Jobs
 - Click “Print” on the computer is much faster than actually printing (build a backlog)
 - Each job is processed in the order it's received (FIFO)
 - Why would you want a print queue rather than a print stack
- Seating customers at a restaurant
- Anything that involves "waiting in line"
- Helpful to decouple producers and consumers

Last-In, First-Out (LIFOs)

STACK ADT


Stack ADT

- Stack: A list of items where insertion and removal only occurs at one end of the list
- Examples:
 - A stack of boxes where you have to move the top one to get to ones farther down
 - A spring-loaded plate dispenser at a buffet
 - A PEZ dispenser
 - Your e-mail inbox
- Stacks are LIFO
 - Newest item at top
 - Oldest item at bottom



Stack Operations

- What member functions does a Stack have?
 - push(item) – Add an item to the top of the Stack
 - pop() - Remove the top item from the Stack
 - top() - Get a reference to the top item on the Stack (don't remove it though!)
 - size() - Get the number of items in the Stack
- What member data does a Stack have?
 - A list of items
 - Top/Last Item Pointer/Index



A Stack Class

- A sample class interface for a Stack
- How should you implement a Stack?
 - Back it with an array
 - Back it with a vector
 - Back it with a linked list
 - Inherit from linked list
 - Which is best?
- Stack Error Conditions
 - Stack Underflow – The name for the condition where you call pop on an empty Stack
 - Stack Overflow – The name for the condition where you call push on a full Stack (a stack that can't grow any more)

```
#ifndef STACKINT_H
#define STACKINT_H

class StackInt {
public:
    StackInt();
    ~StackInt();
    int size() const;
    bool empty() const;
    void push(const int& value);
    void pop();
    int const & top() const;
};
#endif
```

Array Based Stack

- A sample class interface for a Stack
- If using an array list, which end should you use as the "top"?
 - Front or back?
- If using a linked list, which end should you use?
 - If you just use a head pointer only?
 - If you have a head and tail pointer?

```
#ifndef STACKINT_H
#define STACKINT_H

class StackInt {
public:
    Stack();
    ~Stack();
    int size() const;
    bool empty() const;
    void push(const int& value);
    void pop();
    int const& top() const;
private:
    AListInt mylist_;
    // or LListInt mylist_;
};
#endif
```

Stack Examples

- Reverse a string

```
#include <iostream>
#include <string>
#include "stack.h"
using namespace std;
int main()
{
    StackChar s;

    string word;
    cout << "Enter a word: ";
    getline(cin,word);


    for(int i=0; i < word.size(); i++)
        s.push(word.at(i));

    while(!s.empty()){
        cout << s.top();
        s.pop();
    }
}
```


Type in: "hello"
Output: "olleh"

Another Stack Example

- Depth First Search (See Graph Traversals later in this semester)
- Use a stack whenever you encounter a decision, just pick and push decision onto stack. If you hit a dead end pop off last decision (retrace steps) and keep trying, etc.
 - Strait or Left
 - Choose straight...dead end
 - Pop straight and make next choice...left
 - Strait or Right...etc.



<http://www.pbs.org/wgbh/nova/einstein/images/lrk-maze.gif>




Stack Usage Example


- Check whether an expression is properly parenthesized with '(', '[', '{', '}', ']', ')'
 - Correct: $(7 * [8 + [9/\{5-2\}]])$
 - Incorrect: $(7*8$
 - Incorrect: $(7*8]$
- Note: The last parentheses started should be the first one completed
- Approach
 - Scan character by character of the expression string
 - Each time you hit an open-paren: '(', '[', '{' **push** it on the stack
 - When you encounter a ')', ']', '}' the **top** character on the stack should be the matching opening paren type, otherwise ERROR!

$(7 * [8 + [9/\{5-2\}]])$

([[{ }]])



$(7 * [4 + 2 + 3])$




Double-ended Queues

DEQUE ADT


The Deque ADT

- **Double-ended queues**
- Equally good at pushing and popping on either end



STL Deque Class

- Similar to vector but allows for push_front() and pop_front() options
- Useful when we want to put things in one end of the list and take them out of the other



```

#include <iostream>
#include <deque>

using namespace std;

int main()
{
    deque<int> my_deq;
    for(int i=0; i < 5; i++){
        my_deq.push_back(i+50);
    }
    cout << "At index 2 is: " << my_deq[2] ;
    cout << endl;



    for(int i=0; i < 5; i++){
        int x = my_deq.front();
        my_deq.push_back(x+10);
        my_deq.pop_front();
    }
    while( ! my_deq.empty()){
        cout << my_deq.front() << " ";
        my_deq.pop_front();
    }
    cout << endl;
}
    
```

STL Vector vs. Deque

- `std::vector` is essentially a Dynamic Array List
 - Slow at removing and inserting at the front or middle
 - Fast at adding/remove from the back
 - Implies it could be used well as a (stack / queue)
- `std::deque` gives fast insertion and removal from front and back along with fast random access (i.e. `at(i)`)
 - Almost has "look and feel" of linked list with head and tail pointers providing fast addition/removal from either end
 - Implies it could be used well as a (stack / queue)
 - Practically it is likely implemented as a circular array buffer

Circular Buffers

- Take an array but imagine it wrapping into a circle to implement a deque
- Setup a head and tail pointer
 - Head points at first occupied item, tail at first free location
 - Push_front() and pop_front() update the head pointer
 - Push_back() and pop_back() update the tail pointer
- To overcome discontinuity from index 0 to MAX-1, use modulo operation
 - Index = 7; Index++ should cause index = 0
 - $index = (index + 1) \% MAX$
 - Index = 0; Index-- should cause index = 7
 - $if(--index < 0) index = MAX-1;$
- Get item at index i
 - It's relative to the head pointer
 - Return item at $(head + i) \% MAX$



1.) Push_back()
2.) Push_back()

3.) Push_front()

